



Features

- Made of lightweight double anodized aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable housing, insert, and lens
- Aluminum provides excellent heat dissipation
- Mounting clips and ends are available
- Compatible with all Trulux Tape Light

Available Lengths

78-3/4" (2 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT
- Trulux RGB / RGB+WW

TRULUX™ Mini Flange Slot Channel

Make finished 'Slot' Fixtures that are modern and stylish. The 1/8" flanged edge nearly disappears for a clean 'line of light' look. For Slots that don't go floor to ceiling, use the PE-SLOT-END at each end, framing the top and bottom with the small 1/8" lip. Use PE-FC-ENDS for Slots that do go from floor to ceiling. Three pairs of clips per meter are needed to secure the two parts together, and the lens snaps on as the final piece.

Best suited applications:

Ceilings, wall slots, hallways, corridors, lobbies, theaters, accent lighting

Ordering Information

PE-D.5-2M	1/2" Drywall Rough-in Housing
PE-D.6-2M	5/8" Drywall Rough-in Housing
PE-SLOT-2M	Mini Flange Insert
PE-SLOTLENS-2M	Frosted Polycarbonate UV Lens
PE-SLOT-END	Mini Flange Slot End Cap
PE-SLOT-CLIP	Mini Flange Slot Clip (Required)
PE-FC-END	Drywall Slot Housing End Cap

